

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 August 2001 (30.08.2001)

PCT

(10) International Publication Number
WO 01/63018 A1

(51) International Patent Classification: C25D 17/00

(21) International Application Number: PCT/US00/30031

(22) International Filing Date:
1 November 2000 (01.11.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/511,278 23 February 2000 (23.02.2000) US

(71) Applicant: NU TOOL INC. [US/US]; 1645 McCandless Drive, Milpitas, CA 95035 (US).

(72) Inventors: UZOH, Cyprian; 625 Parvin Drive, Milpitas, CA 95035 (US). BASOL, Bulent; 3001 Maple Avenue, Manhattan Beach, CA 90266 (US). TALIEH, Homayoun; 2211 Bentley Ridge Drive, San Jose, CA 95138 (US).

(74) Agent: DIEFENDORF, Richard, R.; Evenson, McKenown, Edwards & Lenahan, P.L.L.C., 1200 G Street, N.W., Suite 700, Washington, DC 20005 (US).

(81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PAD DESIGNS AND STRUCTURES FOR A VERSATILE MATERIALS PROCESSING APPARATUS



(57) Abstract: An apparatus (300) capable of assisting in controlling an electrolyte flow and an electric field distribution used for processing a substrate (10) is provided. It includes a rigid member (320) having a top surface of a predetermined shape and a bottom surface. The rigid member (320) contains a plurality of channels (324), each forming a passage from the top surface to the bottom surface, and each allowing the electrolyte and electric field flow therethrough. A pad (330) is attached to the rigid member via a fastener. The pad also allows for electrolyte and electric field flow therethrough to the substrate (10).

WO 01/63018 A1